



SAFETY DATA SHEET

Version 3.0 Revision Date 09/04/2017

1. PRODUCT AND COMPANY IDENTIFICATION

1.1Product identifiers

Product name

Graphite

Brand

SAM

CAS-No.

: 7782-42-5

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Stanford Advanced

Company

: Materials

23661 Birtcher Dr. Lake Forest, CA 92630

USA

Telephone

+1 (949) 407-8904

Fax

+1 (949) 812-6690

1.4 Emergency telephone number

Emergency Phone #

+1 (949) 407-8904

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Not a hazardous substance or mixture.

2.2 GHS Label elements, including precautionary statements

Not a hazardous substance or mixture.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1Substances

Formula

C

Molecular weight

12.01 g/mol

CAS-No. EC-No. 7782-42-5 231-955-3

Hazardous components

Component				Classification			Cond	Concentration		
Graphite	: ' '	.:	 : ' '	 	: ' '	.:		: ' '		
							<= 1	00 %		

4. FIRST AID MEASURES

4.1 Description of first aid measures

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration.

In case of skin contact

Wash off with soap and plenty of water.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment

needed No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

No data available

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Avoid dust formation. Avoid breathing vapours, mist or gas.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Sweep up and shovel. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs. Provide appropriate exhaust ventilation at places where dust is formed.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL

PROTECTION 8.1 Control parameters

Components with workplace control parameters

Graphite	Component		CAS-No.	Value	Control	Basis				
Remarks Based on impinger samples counted by light-field techniques. mppof X 35.3 = million particles per cubic meter = particles per c.c TWA 2.500000 USA. NIOSH Recommended Exposure Limits Exposure Limits Limits for Air Contaminants Cost Contaminants Cost Cos	One milita		7700 40 5	T\A/A	parameters	LICA Commentional Francisco Liceita				
Remarks Based on impinger samples counted by light-field techniques. mppcf X 35.3 = million particles per cubic meter = particles per c.c TWA 2.500000 USA. NIOSH Recommended Exposure Limits Also see specific listing for Graphite (synthetic). TWA 15.00000 USA. Occupational Exposure Limits GOSHA) - Table Z-1 Limits for Air Contaminants TWA 5.00000 USA. Occupational Exposure Limits GOSHA) - Table Z-1 Limits for Air Contaminants TWA 2.00000 USA. Occupational Exposure Limits GOSHA) - Table Z-1 Limits for Air Contaminants TWA 2.00000 USA. ACGIH Threshold Limit Values mg/m3 (TLV) Pneumoconiosis TWA 2.5 mg/m3 USA. NIOSH Recommended Exposure Limits Also see specific listing for Graphite (synthetic). See table Z-3 TWA 15Million Darticles per cubic meter particles per cubic foot Based on impinger samples counted by light-field techniques. mppcf X 35.3 = million particles per cubic meter = particles per c.c TWA 2 mg/m3 USA. ACGIH Threshold Limit Values (TLV) Pneumoconiosis PEL 10 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107)	Graphite		7782-42-5	IVVA	n particles per					
mppcf X 35.3 = million particles per cubic meter = particles per c.c TWA 2.500000 USA. NIOSH Recommended Exposure Limits Also see specific listing for Graphite (synthetic). TWA 15.00000 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants TWA 5.00000 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants TWA 2.00000 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants TWA 2.000000 USA. ACGIH Threshold Limit Values mg/m3 (TLV) Pneumoconiosis TWA 2.5 mg/m3 USA. NIOSH Recommended Exposure Limits Also see specific listing for Graphite (synthetic). See table Z-3 TWA 15Million USA. Occupational Exposure Limits Also see specific listing for Graphite (synthetic). See table Z-3 TWA 15Million USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts (OSHA) - Table Z-3 Mineral Dusts (USA) -			Remarks	Based on im		unted by light-field techniques				
Mg/m3 Exposure Limits			Romano	mppcf X 35.3 = million particles per cubic meter = particles per c.c						
Also see specific listing for Graphite (synthetic). TWA		: ' '	1	TWA	1	USA. NIOSH Recommended				
TWA 15.00000					Ü					
mg/m3 (OSHA) - Table Z-1 Limits for Air Contaminants TWA 5.000000 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants TWA 2.000000 USA. ACGIH Threshold Limit Values (TLV) Pneumoconiosis TWA 2.5 mg/m3 USA. NIOSH Recommended Exposure Limits Also see specific listing for Graphite (synthetic). See table Z-3 TWA 15Million particles per cubic foot Based on impinger samples counted by light-field techniques. mppcf X 35.3 = million particles per usic meter = particles per c.c TWA 2 mg/m3 USA. ACGIH Threshold Limit Values (TLV) Pneumoconiosis PEL 10 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107)										
mg/m3 (OSHA) - Table Z-1 Limits for Air Contaminants TWA 2.000000 USA. ACGIH Threshold Limit Values mg/m3 (TLV) Pneumoconiosis TWA 2.5 mg/m3 USA. NIOSH Recommended Exposure Limits Also see specific listing for Graphite (synthetic). See table Z-3 TWA 15Million particles per cubic foot Based on impinger samples counted by light-field techniques. mppcf X 35.3 = million particles per cubic meter = particles per c.c TWA 2 mg/m3 USA. ACGIH Threshold Limit Values (TLV) Pneumoconiosis PEL 10 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 3.5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 3.5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 3.5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107)				TWA	1	(OSHA) - Table Z-1 Limits for Air				
mg/m3 (TLV)	:	٠	i. :	TWA		(OSHA) - Table Z-1 Limits for Air				
Pneumoconiosis TWA 2.5 mg/m3 USA. NIOSH Recommended Exposure Limits Also see specific listing for Graphite (synthetic). See table Z-3 TWA 15Million particles per cubic foot Based on impinger samples counted by light-field techniques. mppcf X 35.3 = million particles per cubic meter = particles per c.c. TWA 2 mg/m3 USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts (OSHA) - Table Z-3 Mineral Dusts (USA. ACGIH Threshold Limit Values (TLV) Pneumoconiosis PEL 10 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107)				TWA		USA. ACGIH Threshold Limit Values				
TWA 2.5 mg/m3 USA. NIOSH Recommended Exposure Limits Also see specific listing for Graphite (synthetic). See table Z-3 TWA 15Million particles per cubic foot Based on impinger samples counted by light-field techniques. mppcf X 35.3 = million particles per cubic meter = particles per c.c TWA 2 mg/m3 USA. ACGIH Threshold Limit Values (TLV) Pneumoconiosis PEL 10 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107)						[(TLV)				
Also see specific listing for Graphite (synthetic). See table Z-3 TWA 15Million particles per cubic foot Based on impinger samples counted by light-field techniques. mppcf X 35.3 = million particles per cubic meter = particles per c.c TWA 2 mg/m3 USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts USA. ACGIH Threshold Limit Values (TLV) Pneumoconiosis PEL 10 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants		111								
Also see specific listing for Graphite (synthetic). See table Z-3 TWA 15Million particles per cubic foot Based on impinger samples counted by light-field techniques. mppcf X 35.3 = million particles per cubic meter = particles per c.c TWA 2 mg/m3 USA. ACGIH Threshold Limit Values (TLV) Pneumoconiosis PEL 10 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants				TWA	2.5 mg/m3					
See table Z-3 TWA 15Million particles per cubic foot Based on impinger samples counted by light-field techniques. mppcf X 35.3 = million particles per cubic meter = particles per c.c TWA 2 mg/m3 USA. ACGIH Threshold Limit Values (TLV) Pneumoconiosis PEL 10 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants				1						
TWA			.'			phite (synthetic).				
particles per cubic foot Based on impinger samples counted by light-field techniques. mppcf X 35.3 = million particles per cubic meter = particles per c.c TWA 2 mg/m3 USA. ACGIH Threshold Limit Values (TLV) Pneumoconiosis PEL 10 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants										
mppcf X 35.3 = million particles per cubic meter = particles per c.c TWA 2 mg/m3 USA. ACGIH Threshold Limit Values (TLV) Pneumoconiosis PEL 10 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107)	:	٠	1.	IWA	particles per					
TWA 2 mg/m3 USA. ACGIH Threshold Limit Values (TLV) Pneumoconiosis PEL 10 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107)				Based on im	pinger samples co	unted by light-field techniques.				
Pneumoconiosis PEL 10 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107)				mppcf X 35.3	per cubic meter = particles per c.c					
PEL 10 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants		: ' '	.: : : :	TWA	2 mg/m3	USA. ACGIH Threshold Limit Values (TLV)				
PEL 10 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants				Pneumoconi	osis	,				
PEL 5 mg/m3 California permissible exposure limits for chemical contaminants (Title 8, Article 107) PEL 2.5 mg/m3 California permissible exposure limits for chemical contaminants	.**					limits for chemical contaminants				
PEL 2.5 mg/m3 (Title 8, Article 107) California permissible exposure limits for chemical contaminants				PEL	5 mg/m3	California permissible exposure				
limits for chemical contaminants	:	· · · ·		·	1					
				PEL	2.5 mg/m3					

8.2 Exposure controls

Appropriate engineering controls

General industrial hygiene practice.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact Material: Nitrile rubber

Minimum layer thickness: 0.11 mm Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method:

EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Respiratory protection is not required. Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN 143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Do not let product enter drains.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties 9.1

Appearance Form: flakes Colour: grey b) Odour odourless c) Odour Threshold No data available d) pН No data available Melting point/freezing Melting point/range: 3,652 - 3,697 °C (6,606 - 6,687 °F) - lit. point Initial boiling point and No data available boiling range No data available Flash point g) h) No data available Evaporation rate Flammability (solid, gas) No data available i) Upper/lower No data available flammability or explosive limits Vapour pressure No data available Vapour density No data available

m) Relative density 1.900 g/cm3 Water solubility slightly soluble Partition coefficient: n-No data available

octanol/water Auto-ignition No data available

temperature Decomposition No data available temperature

No data available r) Viscosity

s) Explosive properties t)

No data available

Oxidizing properties

No data available

9.2 Other safety information

No data available

10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

No data available

10.5 Incompatible materials

Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - female - > 2,000 mg/kg

(OECD Test Guideline 423)

LC50 Inhalation - Rat - male and female - 4 h - 2,000 mg/m3

(OECD Test Guideline 403)

Dermal: No data available

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation

(OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation (OECD Test Guideline 405)

Respiratory or skin sensitisation

- Mouse

Did not cause sensitisation on laboratory animals.

(OECD Test Guideline 429)

Germ cell mutagenicity

in vitro assay

S. typhimurium

Result: negative

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified

as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a

known or anticipated carcinogen by NTP.

OSHA:

No component of this product present at levels greater than or equal to 0.1% is identified as

a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

No data available

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

Repeated dose

Rat - male - Feed - NOAEL: 813 mg/kg

toxicity

RTECS: MD9659600

To the best of our knowledge, the chemical, physical, and toxicological properties have not been

thoroughly investigated.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Toxicity to fish

semi-static test LC50 - Danio rerio (zebra fish) - > 100 mg/l - 96 h

(OECD Test Guideline 203)

(OECD Test Guideline 202)

Toxicity to daphnia and

static test EC50 - Daphnia magna (Water flea) - > 100 mg/l - 48 h

static test EC50 - Pseudokirchneriella subcapitata - > 100 mg/l - 72 h

other aquatic

invertebrates

Toxicity to algae

(OECD Test Guideline 201)

12.2 Persistence and degradability

No data available

12.3 **Bioaccumulative potential**

No data available

12.4 Mobility in soil

No data available

Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

Not dangerous goods

IMDG

Not dangerous goods

IATA

Not dangerous goods

15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

No SARA Hazards

Massachusetts Right To Know Components

	,	' '	CAS-No.	'	Revision Date
Graphite			7782-42-5		1989-08-11
Pennsylvania Right To Know Components					
	'	'	CAS-No.	'	Revision Date
Graphite			7782-42-5		1989-08-11
New Jersey Right To Know Components	:.	:	1	1	
			CAS-No.		Revision Date
Graphite			7782-42-5		1989-08-11

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION

HIVIIS Rating	,
Health hazard:	0
Chronic Health Hazard:	
Flammability:	0
Physical Hazard	0
NFPA Rating	
Health hazard:	0
Fire Hazard:	0, , ,
Reactivity Hazard:	0

Further information

This material safety data sheet is offered solely for your information, consideration, and investigation. Stanford Advanced Materials provides no warranties, either express or implied, and assumes no responsibility for the accuracy or completeness of the data contained herein.

			• :			• :		.**			. * *			
٠	1,	:'	٠	:,	:'	٠	1.	:	٠	:,	:"	٠	1,	:'
	:	:.	:	:			:			:			:	
		.**												
١	:.	:	1	1.	:"		÷.	:"	٠	÷.	:	1	1.	:'
	:		: ' '	;		: ' '	:			:		;**	:	
	:,	:	1	1,	:	1	1.	:	1	1,	:"	1	1,	:
	.:		: ' '	.:		: ' '	.:		: ' '					
		:												
		:			:			;			;			;
	.:	:	: ' '	.:	:	: ' '	.:	: .	: ' '	.:	: .	: ' '	.1	: .
			• :					.00	. :					
٠.,	:,	:	٠	:,	:		:,	:'	٠	:,	:	1	1,	;
	.;		: "	.:	: .	: "	.:	: .		.:		111	.:	
		.**	• :		.**	• :			. :					
٠.,	1,	:	٠	:.	:	٠	1.	:"	٠	:.	:"	1	1,	:'
													Page 8 d	
	.:	:.	: ' '	.:	: .	: ' '	.;	: .		.:	: .	:''		